

Packaging item:

Closure N2 REL

Date:

1-7-2011

Internal code:

N/A

| General product specification | | |
|-------------------------------|---|-------------|
| Description | N2 | |
| | Extendable closure for metal containers with tot drainage piercing 32 mm | |
| | REL. Two piece, PE made. Flexible pull-up spout, with tamper evidence | |
| | tear-off seal. Screw cap with bore seal and pull-up handle. | |
| Product properties | | |
| Components | LDPE | |
| | HDPE | |
| Storage | | |
| Storage temperature | Minimum | 10°C |
| | Maximum | 28°C |
| | Direct UV-light during storage must be avoided. The closure should not be subject to penetrating odours or excessive temperature fluctuations. | |
| | Mus Verpakkingen BV recommends not to store 2 pallets upon the other. | |
| Application | | |
| Application temperature | Minimum | 18°C |
| | Maximum | 28°C |
| | The application of closures as specified herein does not relieve the customer from his province to set the capping equipment as required and to conduct his own compatibility test of the applied closure and the product filled. | |
| | The bottle neck or orifice must be true to size and in compliance. | |
| | Technical assistance can be provided by Mus Verpakkingen BV. | |
| Packaging | | |
| Weight (gr) | 6,57 gr ± 10% | |
| Packaging | Carton 3.000 | pcs./carton |
| | Cartons/pallet | 20 |
| Remarks | | |
| Tolerances | Customer drawing tolerances relate to the results of measurement averages, except for ovality. Ovality tolerances depend upon transport conditions, packaging media, vibration and temperature. | |

