

Packaging item:

Closure N2 DIN

Date:

1-7-2011

Internal code:

N/A

General product specification		
Description	N2	
	Extendable press-in closure for tin-plate containers, two piece, for 32 mm	
	DIN-piercing. PE made. Flexible pull-up spout, with tamper evidence	
	tear-off seal. Screw cap with bore seal and pull-up handle.	
Product properties		
Components	Resin LDPE	
	Resin HDPE General	
	Resin EVA General	
	Resin additive	
Storage		
Storage temperature	Minimum	10°C
	Maximum	28°C
	Pallets should be stores in a clean dry area away from UV light, smells and	
	high temperature variations. Pallets should not be double stacked.	
Application		
Application temperature	Mininum	18°C
	Maximum	28°C
	Max. head pressure	250N
	Meeting the above requirements does not absolve the customer from the	
	to set up the capping equipment as required and from carrying out	
	compatibility tests between the applied closure and filled product.	
	Technical assistance can be provided by Mus Verpakkingen BV.	
Packaging		
Weight (gr)	6,20 gr ± 10%	
Packaging	Carton 3.000	pcs./carton
	Cartons/pallet	20
Remarks		
Tolerances	Customer drawing tolerances relate to the results of measurement averages,	
	except for ovality. Ovality tolerances depend upon transport conditions,	
	packaging media, vibration and temperature.	

