

Packaging item:

KR VUN

Date:

1-7-2011

Internal code:

N/A

| General product specification | | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| Description | KR VUN | |
| | One piece tube for the UN SK 30/15 CR closures | |
| Product properties | | |
| Components | Resin LLDPE | |
| Storage | | |
| Storage temperature | Minimum | 10°C |
| | Maximum | 28°C |
| | Pallets should be stored in a clean dry area from UV light, smels and high temperature variations. Pallet should not be double stacked. | |
| Application | | |
| Application temperature | Mininum | 18°C |
| | Maximum | 28°C |
| | Max. head pressure | 250 N |
| | Meeting the above requirements does not absolve the customer form the requirement to set up the capping equipment as required and from carrying out compatibility tests between the applied closure and filled product. | |
| | Technical assistance can be provided by Mus Verpakkingen BV. | |
| Packaging | | |
| Weight (gr) | 6,60 gr ± 10% | |
| Packaging | Carton 750 | pcs./carton |
| | Cartons/pallet | 20 |
| Remarks | | |
| Tolerances | Customer drawing tolerances relate to the results of measurement averages, except for ovality. Ovality tolerances depend upon transport conditions, packaging media, vibration and temperature. | |

