

**Packaging item:**

Closure VU 69/13 SK 60/12

**Date:**

1-7-2011

**Internal code:**

N/A

General product specification		
Description	VU 69/13 SK 60/12	
	Flat press-in closure for metal containers and metal pails with 69mm piercing, two piece, PE made. Base with tamper evidence tear-off seal and rounded thread for glutinous liquids. Flat screw-in plug with recessed handle and bore seal.	
Product properties		
Components	Resin LDPE	
	Resin HDPE General	
	Resin additive	
Storage		
Storage temperature	Minimum	10°C
	Maximum	28°C
	Direct UV-light during storage must be avoided. The closure should not be subject to penetrating odours or excessive temperature fluctuations.	
	Mus Verpakkingen BV recommends not to store 2 pallets upon the other.	
Application		
Application temperature	Mininum	18°C
	Maximum	28°C
	Meeting the above requirements does not absolve the customer from the requirement to set up the capping equipment as required and from carrying out compatibility test between the applied closure and filled product.	
	Technical assistance can be provided by Mus Verpakkingen BV.	
Packaging		
Weight (gr)	24,72 gr ± 10%	
Packaging	Carton 1.000	pcs./carton
	Cartons/pallet	20
Remarks		
Tolerances	Customer drawing tolerances relate to the results of measurement averages, except for ovality. Ovality tolerances depend upon transport conditions, packaging media, vibration and temperature.	

